



QUARZ GRIP

PIGMENTED ADHERENCE PRIMER



MAIN PROPERTIES

- For outdoor use
- Strong adherence capacity
- Universal pigment
- Contains selected fillers



QUARZ GRIP is a pigmented primer composed of special resins and fillers that can be used as a superficial impregnation coat on brickwork surfaces, evenly spreading and reducing absorption and improving the grip of subsequent finishes. QUARZ GRIP contains selected micro fillers to smooth out treated surfaces.

USAGE INDICATIONS

This product is indicated for use on various types of plasterwork; roughcast, two-coat plasterwork, and on old paintwork and organic or mineral, dry and compact absorbent finishes. It is ideal for thick coatings from our range or our outdoor water-based paints such as SPECIAL, MASTERPLUS or SILO ACRYL.

PREPARING THE SURFACE

The surface to be treated must be clean, dry and free from all loose parts, such as old flaking paint. In addition, any traces of dirt and mould must be removed with a MUFFA FINISH power wash. Very flaky bases must be pre-treated with our high-penetration fixative FIX ACRYL (see data sheet). Once FIX ACRYL is applied, the wall should not have a shiny appearance, as the product should penetrate into the surface without a film forming. After approximately 4-6 hours, apply QUARZ GRIP.

TECHNICAL CHARACTERISTICS

Type of binder:	Synthetic copolymers in emulsion
Colour:	White
Appearance:	Thixotropic
Appearance of the film:	Matte
Specific weight:	Kg/l 1.600 ± 0.04 white base
VOC:	< 40 (Directive 2004/42/CE) - (cat. A/a/BA) Max. 40g/l (2010)
Yield:	8 - 10 mq/l manually



QUARZ GRIP

PIGMENTED ADHERENCE PRIMER



INDICATIONS FOR APPLICATION

Ambient conditions and surface conditions:

Do not apply where there is surface condensation or direct sunlight.

Ambient temperature:

Minimum + 5° C – Maximum +35° C

Surface temperature:

Minimum + 5° C – Maximum +35° C

The product can be applied:

With a brush or roller

Dilute with 30% to 40% water.

Equipment cleaning:

Wash with water immediately after use.

DRYING OR HARDENING AT 20°C AND WITH 65 % R.U. (relative humidity)

Touch dry time

30-40 minutes

Complete visible drying time

2-3 h

Wait time before re-coating

after 4 - 6 h

PACKS

5 l and 14 l buckets.

Colours can be realised with the Tintometrico Colorplus system in the Mister Color chart

STORAGE

When the product is stored in its original, tightly sealed containers it will remain stable for at least 12 months, provided it is stored at a temperature of between +5°C and +35°C.

Frost sensitive

SAFETY INSTRUCTIONS

Pursuant to Directive 67/548/CEE, 1999/45/CE and/or Regulation 1272/2008 (CLP) as amended, the product is not labelled. For full information on handling the product and how to dispose of it correctly, please refer to the Safety Sheet.